

FIR		Fir alama BEC CUT L				
Rezistenta	Diametru	K125	K160	K200	P5	P10
380 N/mm ²	Ø0,25 mm	-	X	O	-	-
500 N/mm ²	Ø0,10 mm	O	-	-	-	-
	Ø0,15 mm	-	O	-	-	-
	Ø0,20 mm	-	X	X	-	-
	Ø0,25 mm	O	X	X	X	X
	Ø0,30 mm	O	O	O	O	O
950 N/mm ²	Ø0,10 mm	O	-	-	-	-
	Ø0,15 mm	-	O	-	-	-
	Ø0,20 mm	O	X	X	O	O
	Ø0,25 mm	O	X	X	X	X
	Ø0,30 mm	O	X	O	O	O

X = In stoc permanent

O = La comandă

FIR		Fir Hitachi HBZ-U (N)				
Tip	Diametru	K125	K160	K200	P5	P10
HBZ-U (N)	Ø0,10 mm	X	-	-	-	-
	Ø0,15 mm	O	X	-	-	-
	Ø0,20 mm	O	X	X	O	O
	Ø0,25 mm	-	X	X	X	X
	Ø0,30 mm	-	O	O	O	O

X = In stoc permanent

O = La comandă

FIR		Fir Zincat BEC CUT Z (Tip A)				
Rezistenta	Diametru	K125	K160	K200	P5	P10
500 N/mm ²	Ø0,20 mm	-	O	-	-	-
	Ø0,25 mm	-	X	O	-	-
	Ø0,30 mm	-	O	-	-	-
950 N/mm ²	Ø0,15 mm	-	X	O	-	-
	Ø0,20 mm	-	X	O	-	-
	Ø0,25 mm	-	X	X	-	-
	Ø0,30 mm	-	O	X	-	-

X = In stoc permanent

O = La comandă

FIR		Fir X				
Rezistenta	Diametru	K125	K160	K200	P5	P10
500 N/mm ²	Ø0,20 mm	-	O	O	-	-
	Ø0,25 mm	X	X	X	-	-
	Ø0,30 mm	-	O	O	-	-

X = In stoc permanent

O = La comandă

FIR		Fir Fin	
Tip de fir	Diametru	Lungime	Forma livrare
Tungsten	Ø0,02 mm	3000 m	Bobină
	Ø0,03 mm	3000 m	
	Ø0,05 mm	5000 m	
	Ø0,07 mm	5000 m	
SP Wire (AP Wire)	Ø0,05 mm	5000 m	
	Ø0,05 mm	10000 m	
	Ø0,07 mm	5000 m	
	Ø0,07 mm	10000 m	